Print date: 28.03.2017
Revision date: 28.03.2017

SAFETY DATA SHEET

According to Regulation (EC) n º 1907/2006 and its amendments

*

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name:** C-FLOOR E400 SL
· **Component:** CURE

· **Article number:** 7F-402.9999
· **Version number:** 8
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture:** Hardener

· **1.3 Details of the supplier of the safety data sheet**

· **Identification of the company/undertaking:**

CIN - Corporação Industrial do Norte, S.A. - Av de Dom Mendo, nº 831 (antes EN13 km6)
4474-009 Maia - Portugal - Tel. + (351) 22 940 5000 - customerservice@cin.com

CIN Valentine, S.A.U. - P. I. Can Milans - Riera Seca, 1 - 08110 Montcada i Reixac - España
Tel. + (34) 93 565 66 00 - customerservice.es@cin.com

CIN Celliose, S.A. - Chemin de la Verrerie - BP 58 - 69492 Pierre Bénite Cedex - France
Tel. + (33) (0) 472 397 777 - customerservice.fr@cin.com

· **Further information obtainable from:**
E-mail address of the competent person responsible for the Safety Data Sheet: msds@cin.com

· **1.4 Emergency telephone number:**

Portugal:
- Company: + (351) 22 940 5000
- Antipoison Information Center: + (351) 808 250 143
- Emercency Service (24 hours): + (351) 21 352 4765
Spain:
- Company + (34) 93 565 66 00
France:
- Company ORFILA: + (33) 01 45 42 59 59

*

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Print date: 28.03.2017
Revision date: 28.03.2017

SAFETY DATA SHEET

According to Regulation (EC) n º 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 1)

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms**

GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**
3-aminomethyl-3,5,5-trimethylcyclohexylamine
Benzyl alcohol
cardanol
benzyldimethylamine
2,4,6-tris(dimethylaminomethyl)phenol
· **Hazard statements**
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.
· **Precautionary statements**
Do not breathe dusts or mists.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Dispose of contents/container in accordance with regional/national regulations.
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**		
CAS: 100-51-6 Reg.nr.: 01-2119492630-38	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 2855-13-2 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	25-50%
	poliamina alifática Aquatic Chronic 2, H411	10-25%

(Contd. on page 3)

SAFETY DATA SHEET

According to Regulation (EC) n ° 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 2)

CAS: 8007-24-7 Reg.nr.: 01-2119502450-57	cardanol Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%
CAS: 103-83-3 Reg.nr.: 012119529232-48	benzyldimethylamine Flam. Liq. 3, H226; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Aquatic Chronic 3, H412	2.5-10%
CAS: 90-72-2 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:**
Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
· **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** It might be necessary to use self-contained respiratory protective device.

*

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

SAFETY DATA SHEET
According to Regulation (EC) n ° 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 3)

Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **7.3 Specific end use(s)** No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**
· **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
· **Respiratory protection:** Not required.
· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**

(Contd. on page 5)

SAFETY DATA SHEET

According to Regulation (EC) n ° 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Colour:	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	200 ℃
· **Flash point:**	131 ℃
· **Flammability (solid, gas):**	Not applicable.
· **Ignition temperature:**	435 ℃
· **Decomposition temperature:**	Not determined.
· **Auto-ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	1.3 Vol %
Upper:	13.0 Vol %
· **Vapour pressure at 20 ℃:**	0.1 hPa
· **Density at 20 ℃:**	0.993 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Solids content (w/w):**	64.3 %

(Contd. on page 6)

SAFETY DATA SHEET

According to Regulation (EC) n º 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 5)

· **9.2 Other information:** No further relevant information available.
· **9.3 Other information:** The provisions of directive 2004/42/CE on VOC apply to this product. Refer to the product label and /or technical data sheet for further information.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity**
Harmful if swallowed.

· **LD/LC50 values relevant for classification:**		
CAS: 100-51-6 Benzyl alcohol		
Oral	LD50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1030 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
poliamina alifática		
Dermal	LD50	> 2000 mg/kg (rabbit) > 5000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
· **Serious eye damage/irritation**
Causes serious eye damage.
· **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)

SAFETY DATA SHEET

According to Regulation (EC) n ° 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 6)

*

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**	
CAS: 100-51-6 Benzyl alcohol	
EC50/24 h	390 mg/l (bacterium)
EC50/48 h	230 mg/l (daphnia magna)
EC50/72 h	700 mg/l (algae)
LC50/96 h	460 mg/l (fish)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
EC50/48 h	23 mg/l (daphnia magna)
EC50/72 h	> 50 mg/l (algae)
	37 mg/l (desmodesmus suspicatus)
LC50/96 h	110 mg/l (fish)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Harmful to fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Harmful to aquatic organisms
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

*

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Disposal must be made according to official regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information

· **14.1 UN-Number**	
· **ADR, IMDG, IATA**	UN3066
· **14.2 UN proper shipping name**	
· **ADR**	3066 PAINT

(Contd. on page 8)

SAFETY DATA SHEET

According to Regulation (EC) n ° 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 7)

· **IMDG, IATA**	PAINT
· **14.3 Transport hazard class(es)**	
· **ADR**	
· **Class**	8 (C9) Corrosive substances.
· **Label**	8
· **IMDG, IATA**	
· **Class**	8 Corrosive substances.
· **Label**	8
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	No
· **14.6 Special precautions for user**	Warning: Corrosive substances.
· **Danger code (Kemler):**	80
· **EMS Number:**	F-A,S-B
· **Stowage Category**	A
· **Stowage Code**	SW2 Clear of living quarters.
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **Tunnel restriction code**	E
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 3066 PAINT, 8, III

(Contd. on page 9)

SAFETY DATA SHEET

According to Regulation (EC) n º 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 8)

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Labelling according to Regulation (EC) No 1272/2008** GHS label elements

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **National regulations:**

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:**
CIN - Corporação Industrial do Norte, S.A.
Av de Dom Mendo, nº 831 (antes EN13 km6) - 4474-009 Maia - Portugal
Capital Social € 25.000.000 - C.R.C. da Maia / NIPC: 500 076 936
· **Contact:** See adress in section 1 os this MSDS
· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B

(Contd. on page 10)

SAFETY DATA SHEET

According to Regulation (EC) n º 1907/2006 and its amendments

Trade name: C-FLOOR E400 SL

(Contd. of page 9)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **** Data compared to the previous version altered.***