

**Safety data sheet**  
according to 1907/2006/EC, Article 31





Printing date 19.09.2012

Revision: 19.09.2012

**1 Identification of the substance/mixture and of the company/undertaking**

- **Product identifier**
- **Trade name:** *C-POX S130 FD*
- **Component:** *RESIN*
- **Article number:** *7L-131.7N35*
- **Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the preparation** *Paint*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*CIN - Corporação Industrial do Norte, S.A.*  
*Avenida de Dom Mendo, n° 831*  
*Apartado 1008*  
*4471-909 Maia - Portugal*  
*Tel. 22 940 5000 Fax. 22 948 5661*
- **Further information obtainable from:**  
*Emergency Telephone number:*  
*- Company: (351) 22 940 5000*  
*- Antipoison Information Center: (351) 808 250 143*  
*- Emergency Service (24 hours): (351) 21 352 47 65*
- **Emergency telephone number:**  
*E-mail address of the competent person responsible for the Safety Data Sheet: msds@cin.pt*

**2 Hazards identification**

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  *Xn; Harmful*  
*R20/21: Harmful by inhalation and in contact with skin.*
-  *Xi; Irritant*  
*R38: Irritating to skin.*
-  *Xi; Sensitising*  
*R43: May cause sensitisation by skin contact.*
-  *F; Highly flammable*  
*R11: Highly flammable.*
- **Information concerning particular hazards for human and environment:**  
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*
- **Classification system:**  
*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*
- **Label elements**
- **Labelling according to EU guidelines:**  
*The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.*  
*Dangerous preparations: Directive 1999/45/CE amending by the directive 2001/60/CE.*  
*Material Safety Data Sheet: according to 1907/2006/EC, Article 31*

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

Trade name: C-POX S130 FD

(Contd. of page 1)

· **Code letter and hazard designation of product:**



Xn Harmful  
F Highly flammable

· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight 700-1100)  
xylene (mix)

· **Risk phrases:**

- 11 Highly flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 38 Irritating to skin.
- 43 May cause sensitisation by skin contact.

· **Safety phrases:**

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour/spray.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 Reg.nr.: 01-2119488216-32 01-2119486136-34	xylene (mix) Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 25068-38-6 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight 700-1100) Xi R36/38; Xi R43 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
CAS: 14808-60-7	Quartz (SiO2) Xn R48/20 STOT RE 2, H373	1-2.5%
CAS: 100-41-4 Reg.nr.: 01-2119489370-35	ethylbenzene Xn R20; F R11 Flam. Liq. 2, H225; Acute Tox. 4, H332	1-2.5%
CAS: 108-10-1 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20; Xi R36/37; F R11 R66 Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	1-2.5%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**

(Contd. of page 2)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.  
· **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**

(Contd. of page 3)

- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene (mix)**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**108-10-1 4-methylpentan-2-one**

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Sk, BMGV

· **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Fluid
· <b>Colour:</b>	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	137°C

· **Flash point:** 16°C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 500°C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	1.1 Vol %
· <b>Upper:</b>	7.0 Vol %

· **Vapour pressure at 20°C:** 6.7 hPa

· <b>Density at 20°C:</b>	1.855 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

Trade name: C-POX S130 FD

(Contd. of page 5)

- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Solids content (w/w):** 81.7 %
- **Other information** The provisions of directive 2004/42/CE on VOC apply to this product. Refer to the product label and /or technical data sheet for further information.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Irritant

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**



(Contd. of page 6)

- *Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
*Must not be disposed together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UNI263
· <b>UN proper shipping name</b>	
· <b>ADR</b>	1263 PAINT, special provision 640H
· <b>IMDG, IATA</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids.
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E, S-E
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**

(Contd. of page 7)

**· Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 5L
- **Tunnel restriction code** D/E

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.  
Dangerous preparations: Directive 1999/45/CE amending by the directive 2001/60/CE.  
Material Safety Data Sheet: according to 1907/2006/EC, Article 31

**· Code letter and hazard designation of product:**



Xn Harmful  
F Highly flammable

- **Hazard-determining components of labelling:**  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight 700-1100) xylene (mix)
- **Risk phrases:**  
11 Highly flammable.  
20/21 Harmful by inhalation and in contact with skin.  
38 Irritating to skin.  
43 May cause sensitisation by skin contact.
- **Safety phrases:**  
9 Keep container in a well-ventilated place.  
16 Keep away from sources of ignition - No smoking.  
23 Do not breathe vapour/spray.  
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
51 Use only in well-ventilated areas.  
60 This material and its container must be disposed of as hazardous waste.
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 19.09.2012

Revision: 19.09.2012

**Trade name: C-POX S130 FD**

(Contd. of page 8)

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R36/37 Irritating to eyes and respiratory system.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R66 Repeated exposure may cause skin dryness or cracking.

· **Department issuing MSDS:**

CIN - Corporação Industrial do Norte, S.A.

Sede: Avenida de Dom Mendo, n° 831

Apartado 1008 • 4471-909 Maia – Portugal

Capital Social: € 25.000.000 Euros • C.R.C. da Maia / NIPC: 500 076 936

· **Contact:** See adress in section 1 os this MSDS

· **\* Data compared to the previous version altered.**